

# Fluke T5 Voltage, Continuity and Current Testers

<b>Specifications</b>	
<b>Continuity beeper</b>	<b>Threshold:</b> On at <25 $\Omega$ , off at >400 $\Omega$
<b>Volts indicator LED</b>	<b>Threshold:</b> Guaranteed on by 30V ac
<b>Environmental Specifications</b>	
<b>Operating Temperature</b>	-10 °C to 50 °C
<b>Storage Temperature</b>	-30 °C to 60 °C
<b>Humidity (Without Condensation)</b>	0% to 95% (5 °C to 30 °C) 0% to 75% (30 °C to 40 °C) 0% to 45% (40 °C to 50 °C)
<b>Dust/water resistance</b>	Yes
<b>Operating Altitude</b>	2000 meters max
<b>Temperature Coefficient</b>	0.1 x (specified accuracy)/degree C (<18 °C or >28 °C)
<b>Safety Specifications</b>	
<b>Overvoltage category</b>	<b>T5-600:</b> 600V ac/dc, CAT III <b>T5-1000:</b> 1000V ac/dc, CAT III
<b>Agency Approvals</b>	UL, CSA, and VDE
<b>Maximum voltage</b>	between any terminal and earth ground
<b>Mechanical &amp; General Specifications</b>	
<b>Size</b>	30.5 x 51 x 203 mm
<b>Weight</b>	300g
<b>Warranty</b>	2 years
<b>Battery Life</b>	200 hour zinc chloride, 400 hour alkaline
<b>Battery type</b>	Two AA zinc chloride
<b>Low battery indicator</b>	Yes
<b>Current sensor opening</b>	12.9 mm
<b>Calibration cycle</b>	1 year
<b>Test leads</b>	<b>Type:</b> Heavy duty, flexible leads rated for 1000V use. Field replaceable leads terminate in male shrouded banana plugs <b>Probes:</b> One red, one black. of two tip Detachable Slim-ReachT probe tips in one <b>Styles:</b> TP4 4 mm round